



LGAP90H Asphalt Paver (Hydraulic Transmission)

LGAP90H asphalt paver is used for paving road, plaza and so on, which is with compact structure and easily operated. It uses advanced double sets of hydraulic stretching screed and auto level sensing device to improve the reliability.

Engine	
Model	Cummins 6BTA5.9(UK)
Type	Water cooled, turbocharged
Rated power	138KW
Rated speed	2200rpm
Main Technical Specification	
Basic paving width	2500mm
Max. paving width	9000mm
Max. paving thickness	350mm
Min. paving thickness	20mm
Paving speed	0-12m/min
Max. theoretic productivity	700t/h
Traveling Equipment	
Transmission	Full hydraulic
Under carriage	Track type
Type of Track	
Track length on ground	3050mm
Width	300mm
Working Equipment	
Screed plate	
Basic width	2500mm
Grade adjustment	-1-3%
Extension model	Mechanical
Vibrating frequency	
Frequency	0-50Hz
Hopper	
Capacity	14000kg
Discharge type	Hydraulic
Conveyor	

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Independently driven	
Hydraulic control	
Electric System	
Batteries	2 sets
System voltage	24V
Dimensions	
Overall length	6470mm
Overall width	2600mm
Overall height	3240mm
Main Components	
Hydraulic pump	SAUER
Vibrating motor	SAUER
Control valve	Germany

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572