



QP6015 Tower Crane

Lifting Performance	
Max lifting capacity	8000kg
Radius	60m
Hook height	
Max. height	200m
Hoisting mechanism	
Motor power	30/30KW
Motor Rotate speed	1325/725 (r/min)
Wire rope: Diameter	14m
Wire rope: Max average linear velocity	160m/min
Braking moment	630N.m

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Tel: +86-21-541-71571

E-mail: <mailto:info@shlongji.com>

Fax: +86-21-541-71572

Reducer gear ratio	17.8
Rope capacity	400m
Max tractive force	20KN
Tap position	5
Trolleying mechanism	
Motor power	5.5KW
Motor Rotate speed	1440(r/min)
Wire rope: Diameter	9.3m
Wire rope: Max a linear velocity	60m/min
Reducer gear ratio	33
Braking moment	80N.m
Working radius	65m
Tap position	3
Slewing mechanism	
Motor power	4 x 2 Kw
Motor rotate speed	1440rpm
Reducer ear ratio	195
Reducer output twisting moment	10000N.m
Output gear module	12mm
Output gear number of teeth	16
Tap position	m
Slewing ring	1600.50
climbing mechanism	
Motor power	5.5Kw
Motor rotate speed	1440rpm
Hydraulic pump flow	14.4L/min
Hydraulic pump working pressure	25Mpa
Climbing hydraulic diameter of cylinder/piston	160/110
Climbing hydraulic Max pushing force	45t
Climbing hydraulic speed of climbing	0.7 m/min

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Tel: +86-21-541-71571

E-mail: <mailto:info@shlongji.com>

Fax: +86-21-541-71572